

## Product information Alu-Spray

<b>Description</b>	Silver grey, fast-drying paint for light metal casting.
<b>Field of use</b>	Core shop/moulding shop, fettling shop as well as chill casting.  <b>Alu-Spray</b> is used due to its <u>cooling effect</u> on moulding surfaces. The cores / moulds can be either synthetic resin- and clay-bound or metallic.  The product is used in the casting cleaning shop as a <u>protective varnish</u> and <u>cover varnish</u> for repair areas and for <u>beautification</u> .
<b>Application</b>	Best effect is achieved with an evenly thin coating. Thus homogeneity is assured, <u>shake</u> spray can <u>well before use</u> . Clean nozzle for longer brakes by holding spray can overhead.
<b>Technical Data</b>	Density (20 °C):                      approx. 0,77 g/cm <sup>3</sup> Boiling point:                          approx. -76 °C Flash point:                              approx. -97 °C
<b>Packaging</b>	<b><u>Box with 12 spray cans á 500 ml</u></b>
<b>Storage</b>	Protect <b>Alu-pray</b> from direct sunlight and temperatures above 50 °C. Keep away from open flames and other ignition sources. Pressurised container! Shelf life 24 months when properly stored inside in original unopened container.
<b>Regulations and information</b>	<b>Alu-Spray</b> is classified and labeled according to the CLP regulation and corresponds to the current EC regulation. Information about transport regulations, fire-fighting measures, accidental release, ecology and further information can be found in the material safety data sheet.

All information in this data sheet are based on our current knowledge and experience. A legally binding assurance of certain properties or suitability for a specific purpose cannot be derived. Each user of our products has to verify the usability for its specific purpose in his personal responsibility. Rights must be observed if required.

HN/MT

status 12/23